

























	Standard	Result
 Size	EN ISO 24342	See separate table
 Thickness	EN ISO 24346	2.5 mm
 Wear layer	EN ISO 24340	0.55 mm
Surface treatment		K-Guard+ PU coating
Guarantee <sup>1</sup>	Light industrial	15 years
	Commercial	15 years
	Residential	Lifetime guarantee
 Bevelled edge		Micro
 Mass per unit area	EN ISO 23997	4270 g/m <sup>2</sup>
 Standards	EN 649/EN ISO 10582	Pass
 Classification	EN 685/EN ISO 10874 - Light industrial	42: Light industrial general
	EN 685/EN ISO 10874 - Commercial	33: Commercial heavy
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
 Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
 Staining resistance	EN ISO 26987/EN 423	Excellent
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN 649	Group T
	EN ISO 10582	Type 1
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0.25%)
 Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 2 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
 Castor chair continuous use	EN 425/ISO 4918	Pass
 Thermal resistance	ISO 8302	0.0097 m <sup>2</sup> K/W Suitable for underfloor heating. Max 27°C
 Slip resistance <sup>2</sup>	EN 13893	D5
	DIN 51130	See separate table
	BS7976	> 36
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Adhesive	Karndean Universal	Yes
	Silane	Yes
	Pressure Sensitive	Yes
 Environmental	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions.
	FloorsCore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standard
 Recycling		Suitable
 Phthalate free		Yes

<sup>1</sup> Subject to terms. Please see our website.

<sup>2</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com



21

BS EN 14041: 2004 (DOP 2021/UKCA/OPEnhance/01)
Approved body 0221
Floor coverings (internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582



20

EN 14041: 2004 (DOP 2020/OPEnhance/EN/02)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582





	Product Code	Size		Box Quantity		Slip Resistance	LRV
		mm	inches	m <sup>2</sup>	Pieces	DIN 51130	
Wood Designs	WP313-SR	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R11	16
	WP318-SR	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R11	6
	WP411-SR	1219.2 x 228.6	48.0" x 9.0"	3.345	12 Planks	R11	30
	WP412-SR	1219.2 x 228.6	48.0" x 9.0"	3.345	12 Planks	R10	26
	WP413-SR	1219.2 x 228.6	48.0" x 9.0"	3.345	12 Planks	R11	26
	WP422-SR	1219.2 x 228.6	48.0" x 9.0"	3.345	12 Planks	R11	47
	WP423-SR	1219.2 x 228.6	48.0" x 9.0"	3.345	12 Planks	R11	33
Stone Designs	SP213-SR	457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R11	23
	SP216-SR	457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R11	23
	SP217-SR	457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R11	35
	SP218-SR	457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R11	9